



Water quality handhelds for field work

Oxygen, Conductivity, Salinity, pH, Temperature

- Simple push-button calibration
- Built-in probe storage chamber
- Backlit display for easy viewing in any light
- Convenient multiparameter probe designs
- Automatic temperature compensation
- Water-resistant to IP-65 standard
- Two-year instrument warranty

YSI 55 oxygen & temperature

- Dissolved oxygen in mg/L or % saturation
- Salinity compensation
- Industry standard
- Easy calibration



YSI Model 55 and Model 85 (below)

YSI 85 oxygen, conductivity, salinity, & temperature

- 50-reading memory with ID
- User-selected ranges or autoranging for conductivity
- Automatic salinity compensation
- Screw-on DO membranes



YSI 60 pH & temperature

- 50-reading memory with ID
- Replaceable pH electrode with one-year warranty
- Cable lengths up to 100 feet

YSI 63 pH, conductivity, salinity, & temperature

- 50-reading memory with ID
- Four-electrode conductivity cell
- User-selected ranges or autoranging for conductivity
- Replaceable pH electrode with one-year warranty
- Cable lengths up to 100 feet

YSI 30 & 30M conductivity, salinity, & temperature

- Four-electrode conductivity cell
- User-selected ranges or autoranging for conductivity
- YSI 30M has 50-reading memory with ID (available with 100-foot cables)



YSI Models 30, 60, and 63

Pure Data for a Healthy Planet.®

Convenient field measurement.





To order, or for more information, contact YSI Environmental.

+1 937 767 7241

800 897 4151 (US)

www.ysi.com

YSI Environmental
+1 937 767 7241
Fax +1 937 767 9353
environmental@ysi.com

Endeco/YSI
+1 508 748 0366
Fax +1 508 748 2543
systems@ysi.com

SonTek/YSI
+1 858 546 8327
Fax +1 858 546 8150
inquiry@sontek.com

YSI Environmental Gulf Coast
+1 225 753 2650
Fax +1 225 753 8669
environmental@ysi.com

YSI Hydrodata (UK)
+44 1462 673 581
Fax +44 1462 673 582
europe@ysi.com

YSI Middle East (Bahrain)
+973 1753 6222
Fax +973 1753 6333
halsalem@ysi.com

YSI (Hong Kong) Limited
+852 2891 8154
Fax +852 2834 0034
hongkong@ysi.com

YSI (Qingdao) Limited
+86 532 575 3636
Fax +86 532 571 0101
ysiqd@ysiqd.com.cn

YSI Nanotech (Japan)
+81 44 222 0009
Fax +81 44 221 1102
nanotech@ysi.com

ISO 9001
ISO 14001

Pure Data for a Healthy Planet and Who's Minding the Planet? are registered trademarks of YSI Incorporated.

©2006 YSI Incorporated
Printed in USA 0107 W42-03

YSI incorporated
Who's Minding
the Planet?™

55 oxygen & temperature (System Specifications)

Salinity compensation: 0 to 40 ppt (manual)
Altitude compensation: 0 to 10,000 feet
Cable lengths: 12, 25, 50 feet (3.7, 7.6, 15.2 meters), available with detachable cable

Measurement	Range	Resolution	Accuracy (meter & probe)
Dissolved Oxygen	0-200%	0.1%	±2% saturation
	0-20 mg/L	0.01 mg/L	±0.3 mg/L
Temperature	-5 to +45°C	0.1°C	±0.2°C

85 oxygen, conductivity, salinity & temperature (System Specifications)

Range: Autoranging for dissolved oxygen. User-selected or autoranging for conductivity
Adjustable conductivity reference temperature: 15 to 25°C
Adjustable conductivity temperature compensation factor: 0 to 4%
Salinity compensation: 0 to 80 ppt (automatic)
Altitude compensation: 0 to 10,000 feet
Cable lengths: 10, 25, 50, 100 feet (3, 7.6, 15.2, 30.5 meters), available with detachable cable

Measurement	Range	Resolution	Accuracy (meter & probe)
Dissolved Oxygen	0 to 200%	0.1%	±2% saturation
	0 to 20 mg/L	0.01 mg/L	±0.3 mg/L
Conductivity	0 to 499.9 µS/cm	0.1 µS/cm	±0.5% full scale
	0 to 4999 µS/cm	1 µS/cm	±0.5% full scale
	0 to 49.99 mS/cm	0.01 mS/cm	±0.5% full scale
Salinity	0 to 200.0 mS/cm	0.1 mS/cm	±0.5% full scale
	0 to 80 ppt	0.1 ppt	±2% or ±0.1 ppt
Temperature	-5 to +65°C	0.1°C	±0.1°C (±1 lsd)
	-5 to +45°C for oxygen		

60/63 pH & pH/conductivity & temperature (System Specifications)

pH electrode: Combination with gel reference
Range: Autoranging for pH, user-selected or autoranging for conductivity
Temperature compensation: Automatic
Adjustable conductivity reference temperature: 15 to 25°C
Adjustable conductivity temperature compensation factor: 0 to 4%
Cable lengths: 10, 25, 50, 100 feet (3, 7.6, 15.2, 30.5 meters)

Measurement	Range	Resolution	Accuracy (meter & probe)*
pH	0 to 14	0.01 unit	±0.1 unit within 10°C of calibration ±0.2 unit within 20°C
Conductivity	0 to 499.9 µS/cm	0.1 µS/cm	±0.5% full scale
	0 to 4999 µS/cm	1 µS/cm	±0.5% full scale
	0 to 49.99 mS/cm	0.01 mS/cm	±0.5% full scale
	0 to 200.0 mS/cm	0.1 mS/cm	±0.5% full scale
Salinity	0 to 80 ppt	0.1 ppt	±2% or ±0.1 ppt
Temperature	-5 to +75°C	0.1°C	±0.1°C (±1 lsd)

*Meter accuracy is ±0.02 unit.

30 salinity, conductivity & temperature (System Specifications)

Range: User-selected or autoranging
Adjustable reference temperature: 15 to 25°C
Adjustable temperature compensation factor: 0 to 4%
Cable lengths: 10, 25, 50, 100 feet (3, 7.6, 15.2, 30.5 meters)

Measurement	Range	Resolution	Accuracy (meter & probe)
Conductivity	0 to 499.9 µS/cm	0.1 µS/cm	±0.5% full scale
	0 to 4999 µS/cm	1 µS/cm	±0.5% full scale
	0 to 49.99 mS/cm	0.01 mS/cm	±0.5% full scale
	0 to 200.0 mS/cm	0.1 mS/cm	±0.5% full scale
Salinity	0 to 80 ppt	0.1 ppt	±2% or ±0.1 ppt
Temperature	-5 to +95°C	0.1°C	±0.1°C (±1 lsd)